



600 SERIES

Heavy-Duty Commercial Grade 1 Surface Applied Closers



Standard Features

- **Performance** Complies with ANSI A156.4, Grade 1, 2 million cycles, UL listed
 - **Chassis/Closer** Non-handed, cast aluminum, mounting to regular, top jamb or parallel arm applications
 - **Main Arm** Forged steel, accommodates reveals up to 3 1/4", adjustable extension arm
 - **Spring Power** Adjustable 1 - 4 and 3 - 6 sizes
 - **Backcheck** Adjustable, hydraulic - providing cushioning and preventing uncontrolled openings of the door
 - **Valves** Adjustable, independent, non-critical (sweep and latch), consistent closing speeds
 - **Fasteners** Compatible for aluminum, hollow metal and wood doors and frames
 - **Door Range** Up to 180 degrees
 - **Door Preparation** 9-1/16" horizontal and 3/4" vertical mounting hole locations (retrofits traditional closer)
 - **Warranty** 25 year limited
- #### Optional Features
- **Covers** High impact plastic and plated kit: cover, arm & bracket.
 - **Hold Open Arm** Forged steel with hold open adjustable from 80 to 135 degrees
 - **Sex Nuts** For 1-3/8" or 1-3/4" thick doors

Other View:



TELL MANUFACTURING, INC — Page 14 — 2011

CORPORATE OFFICE: 18 Richard Drive, Lititz, PA 17543 TOLL FREE: 800-433-4047 PHONE: 717-625-2990 FAX: 717-625-7095

OTHER LOCATIONS: HOUSTON, TEXAS ELKHART, INDIANA MIRA LOMA, CALIFORNIA

WEBSITE: www.tellmfg.com