



ML1300 SERIES

Grade 1 Heavy-Duty Commercial Mortise Locksets



Escutcheon Mortise Lock
MR TRIM Boston (BFEF) Trim



Curved Strike

Standard Features

- **Performance** Complies with ANSI A156.13, Series 1000, Grade 1, UL listed for 3 hour fire door ANSI A117.1 American Disabilities Act (ADA), 1,000,000 cycles
- **Chassis** Mortise, steel - coated with zinc dichromate (corrosion resistance), 13 gauge cold rolled steel
- **Lever** Non-handed, field reversible, solid forged brass
- **Trim** Roses, escutcheon, turns (solid forged brass)
- **Latch bolt** Latch 3/4" throw (stainless steel), deadbolt 1" throw (stainless steel), anti-friction
- **Backset** 2-3/4"
- **Strike** 4-7/8" curved strike
- **Door Range** 1-3/4" to 2"
- **Door Preparation** Per function and template
- **Cylinder** Schlage (SCC) - 6-pin solid brass, C keyway, keyed different (KD)
- **Other Cylinder Options** Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)
- **IC Keyway Cylinder** Best A (BA), Best B (BB), Best C (BC), Best D (BD), Best E (BE), Best F (BF), Best G (BG), Best H (BH), Best J (BJ), Best K (BK), Best L (BL), Best M (BM), Best Q (BQ), Best U (BU), Black construction core (BLK), Less core (00), Not specified (XX)
AVAILABLE 6- OR 7-PIN
- **Keys** Two nickel silver per lock cylinder
- **Warranty** 5 year limited

Optional Features

- **Strike** Straight lip (stainless steel)
- **Door Range** 1-3/4" to 2"
- **Cylinder** Other manufacturers including small format interchangeable cores
- **Keying** Grand master key (GMK), construction master key (CMK), master key (MK), keyed different (KD), keyed alike (KA), 0-bitted (0BIT)

TELL MANUFACTURING, INC — Page 9 — 2012

CORPORATE OFFICE: 18 Richard Drive, Lititz, PA 17543 TOLL FREE: 800-433-4047 PHONE: 717-625-2990 FAX: 717-625-7095
OTHER LOCATIONS: HOUSTON, TEXAS ELKHART, INDIANA MIRA LOMA, CALIFORNIA

WEBSITE: www.tellmfg.com