

Heavy-Duty, Commercial Grade 1

DELAYED EGRESS EXIT DEVICE

with Alarm



FEATURES

Designed for use on delayed exit applications and ideal for controlled access areas.

FEATURES:

- Control to Exit
- Nuisance Alarm
- Momentary Exit
- LED Indicator Modes
- Anti-Disassembly Mode
- Internal Alarm Horn
- Remote Alarm
- Fire Alarm Input
- Definable Delay Time

STANDARD FEATURES

Performance	Complies with ANSI A156.3, 2001, Grade 1, UL/ULC Listed
Rail	Fits 30" to 36" doors
Latch Bolt	Stainless steel 3/4" throw with deadlatch feature
Backset	2-3/4"
Strike	Adjustable with slotted holes for adjustments
Cylinder	Standard Schlage (SCC) - 6-pin solid brass, C keyway, keyed different (KD)
Fasteners	Accommodates wood or metal doors with thru bolts standard
Door Range	1-3/4" to 2-1/4" thick
	Surface mounted and covers 161 prep
UL Listed	Fire Rated device available for use on doors rated up to 3 hours
Warranty	Limited lifetime for device; 1 year for electronics

ALARM FEATURES

Hardware	CPU	16 bit
	Keypad	Status switch (up/mid/down) x1
	Input ports	Alarm trigger input x1, tamper detection input x1
	Led Indicator	Led status indicator (red/green/blue) x1
	Beep Tone	103 dB Piezo horn
Electrical Condition	Operating Voltage	12VDC Regulated
	Power Consumption	20uA for Standby, Alarm Trigger 83mA
Environmental	Operating Temperature	-10°C - 50°C / 14 °F - 122° F
	Power Consumption	20uA for Standby, Alarm Trigger 83mA

KEYING OPTIONS FOR SELECT TRIM

Tell Cylinder	Restricted Tell keyway cylinder can key both the cylinder and interchangeable (IC) core in one lock. The cylinders and cores are interchangeable. Tell keyway cylinder is available only keyed to 6-pin.
----------------------	--

REQUIRED ACCESSORIES*

- A regulated power supply with a fire alarm interface. 1 Amp min. @12VDC/set
- Standard electric hinge with the size of 4-1/2" x 4-1/2" or 4-1/2" x 5"; Conductor: 8 conductors

*Not furnished, order separately

ESCUTCHEON TRIM

ITEM	DESCRIPTION	FINISH
EX100342	ESC Entry Escutcheon Lever Trim	US32D/304
EX100343	ESC Entry Escutcheon Lever Trim	US32D/316

