




High Performance Code Lever Lockset

Locks in the CL5000 range are the ultimate standalone electronic door locks. Top of the range digital locks tested to Grade 2.

Heavy-duty locks for use in high traffic applications. Unlike the other electronic locks, the CL5000 has a conventional 3x4 button keypad layout for instant familiarity, providing quick programming with a multiple range of functions. Particularly suitable for use in health, educational, commercial and residential environments.

FEATURES - CL5000

- Allows up to 80 User Codes 4, 5 or 6 digits long
- On door programming
- Allows up to ten one-time User Codes to be entered
- Locked and unlocked LED indicator option
- PVD low maintenance finish
- Over 200,000 operations from 4 x AA cells (supplied)
- Tamper time out and low battery warning
- Connections for remote release by reception desk button
- Alarm release included
- Front change cylinder
- Suitable for internal and external use
- Tested to Grade 2 ANSI A156.2 / A156.25
- Two year limited warranty*



CL5000 Series

FUNCTIONS

CL5210 — Heavy Use Tubular Latch

Medium-duty, stainless steel latchbolt with 'anti-shim' deadlocking plunger, 5/16" follower. Outside lever turns freely without operating the latchbolt. When a valid code is entered and the Blue LED lights up, the lever will retract the latchbolt. When the door closes the spring latch will automatically lock the door. The key will open the door for management functions. The key may be used to set the lock into Code Free mode so that anyone can open the door without using a code (Classroom Function).

CL5000 PK — Panic Kit for Tell Exit Device

A valid code key retracts latchbolt for entry on the Tell 7300 Series, 8300 Series, and 9500 Series exit devices.

APPLICATIONS



Code Change Method

Set via keypad using Master Code

Passage Function

Set via keypad or key

FEATURES - CL5000

- Allows up to 80 User Codes 4, 5 or 6 digits long
- On door programming
- Allows up to ten one-time User Codes to be entered
- Locked and unlocked LED indicator option
- PVD low maintenance finish
- Over 200,000 operations from 4 x AA cells (supplied)
- Tamper time out and low battery warning
- Connections for remote release by reception desk button
- Alarm release included
- Front change cylinder
- Suitable for internal and external use
- Tested to Grade 2 ANSI A156.2 / A156.25
- Two year limited warranty*

TECHNICAL SPECIFICATIONS

Operations 200,000 per set of batteries

Batteries 4 x AA Cells CL5210BB 8 x AAA Cells

Low Battery Warning Red LED will flash on opening to indicate batteries need to be changed

Memory Stores 80 different User Codes

Spindle Type 5/16" spring loaded spindle

Material Zinc Alloy

Door Thickness 13/8" – 23/8"

Buttons Individual stainless steel buttons

Non Handed Locks will fit doors hung on the left or right

Remote Release 1 (Rem 1) option fitted as standard to open lock remotely via cable

Remote Release 2 (Rem 2) option allows connection to alarm release

Fitting Options Vertical

Finish Brushed Steel

Keyed Alike Supplied Keyed Alike on request

Keyway Schlage C, 6-pin standard. Optional SFIC upon request

Codes 4, 5 or 6 digit codes creating up to 1,000,000 unique codes

Standards Tested to Grade 2 ANSI A156.2/A156.25

Suitable for Internal and external use


OPTIONS

Lock Case Options

2¾" backset. US Mortise Door Prep Type 86
Cut-out, ANSI A 115.1

Panic Kit Option (PK)

PK Kit works with most of our rim exit devices.



| Part Number | Model Number | Function |
|-------------|--------------|---------------|
| CL102662 | CL5210 BS | Lever X Lever |
| CL102663 | CL5000PK BS | Exit Trim |

* Tell electronic locks offer a two year warranty and will be repaired, serviced or replaced free of charge if they develop a manufacturing fault. Faults caused by misuse, abuse and/or poor fitting are not covered by the warranty.