

Grade 1 Rim (Narrow Style)

EX9500NS SERIES



Fire-Rated Option Shown

FEATURES

- Performance**
- Complies with ANSI A156.3
 - 2001, Grade 1
 - UL/ULC listed
 - 5lbs Opening force on ADA compliant product

- Rail**
- Fits 30" to 36" doors.

- Latch**
- Stainless steel $\frac{3}{4}$ " throw with deadlatch feature

- Backset**
- 2 $\frac{3}{4}$ "

- Strike**
- Adjustable with slotted holes for adjustments
 - Other strikes available

- Cylinder**
- C keyway (SCC) - 6-pin solid brass, keyed different (KD)

- Fasteners**
- Accommodates wood or metal doors with thru bolts standard

- Door Thickness**
- 1 $\frac{3}{4}$ " to 2 $\frac{1}{4}$ "

- Door Preparation**
- Surface mounted
 - Covers 161 prep

- Finishes**
- Satin Chrome (US26D), Polished Brass (US3)

- Warranty**
- Lifetime limited

EX9500NS SERIES

OPTIONS	
KEYING	6-pin cylinders, can be pinned to 5-pin.
Cylinders	Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Options Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)
Tell Cylinder	Restricted Tell keyway cylinder can key both the cylinder and interchangeable core in one lock. The cylinders and IC cores are interchangeable. Tell keyway cylinder is available only keyed to 6-pin. Tell IC cylinder can be keyed to 6-pin or 7-pin interchangeable core (IC)
IC Keyway Cylinders (Available 6- or 7-Pin)	Best A (BA), Best B (BB), Best C (BC), Best D (BD), Best E (BE), Best F (BF), Best G (BG), Best H (BH), Best J (BJ), Best K (BK), Best L (BL), Best M (BM), Best Q (BQ), Best U (BU), Black construction core (BLK), Less core (00), Not specified (XX)
Keying Options	Grand Master Key (GMK), Construction Master Key (CMK), Master Key (MK), Keyed Different (KD), Keyed Alike (KA), Interchangeable Core uncombined (IC), 0-bitted (0BIT)
EXTERIOR TRIM	Exterior Blank Pull (8PDT), Exterior Pull With Cylinder Cut Out (8P03), Entry Ball Knob Trim (EMP808), Passage Ball Knob Trim (EMP875), Storeroom Ball Knob Trim (EMP886), Entry Lever Trim Without Clutch (CTL), Exterior Thumbpiece Trim (TP81), Pull Trim With Rim Cylinder (PT881), Exterior Escutcheon Lever Trim (ESCH), Heavy-Duty Escutcheon Entry Lever Trim (ESCHHD)
UL LISTED	3 hour fire rated device available
FIRE RATED	Fire rated device available for use on doors rated up to 3 hours. Specify when ordering.
TELL FINISHES	 US26D Satin Chrome  US3 Polished Brass