

Light-Duty Tubular Grade 3

## **KT3500 SERIES**



FEATURES	
Performance	Complies with ANSI A156.2, Series 4000
	Grade 3 light duty
	• 200,000 cycles
Chassis	• Tubular
	Steel - coated with zinc dichromate (corrosion resistance)
Lever	Non-handed, solid cast
Latch	• 1" x 2 ¼", square corner faceplate
	• 1" housing diameter (stainless steel)
	• ½" throw
Rose	• 2 ½" diameter
Backset	Adjustable 2 ¾" or 2 ¾"  Adjustable 2 ¾" or 2 ¾"
Strike	Standard: 2-34" x 1-1/8" standard T-strike
	Optional strikes available
Cylinder	• SCC - C keyway
	• 5-pin solid brass
	Keyed different (KD)
Keys	Two nickel silver per lock cylinder
Door Thickness	- 1 %" - 2"
Door Preparation	• 2 1/8" diameter
	• 1" diameter for latchbolt
Warranty	Limited lifetime

## **KT3500 SERIES**

KEYING	6-pin cylinders, can be pinned to 5-pin.
Cylinders	Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Options Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)
Tell Cylinder	Restricted Tell keyway cylinder available, optional. Tell keyway cylinder is available only keyed to 6-pin.
Keying Options	Grand Master Key (GMK), Construction Master Key (CMK), Master Key (MK), Keyed Different (KD), Keyed Alike (KA), Interchangeable Core uncombinated (IC), 0-bitted (0BIT)
AVAILABLE FUNCTIONS	Entry 81 Privacy Bed/Bath 76 Passage Hall/Closet 75

**TELL FINISHES** 



US32D Satin Stainless Steel

