

Light-Duty Tubular Grade 3
KT3500 SERIES



Empire Knob Style (EMP)

FEATURES

- Performance**
- Complies with ANSI A156.2, Series 4000
 - Grade 3 light duty
 - 200,000 cycles

- Chassis**
- Tubular
 - Steel - coated with zinc dichromate (corrosion resistance)

- Lever**
- Non-handed, solid cast

- Latch**
- 1" x 2 1/4", square corner faceplate
 - 1" housing diameter (stainless steel)
 - 1/2" throw

- Rose**
- 2 1/2" diameter

- Backset**
- Adjustable 2 3/4" or 2 3/8"

- Strike**
- Standard: 2-3/4" x 1-1/8" standard T-strike
 - Optional strikes available

- Cylinder**
- SCC - C keyway
 - 5-pin solid brass
 - Keyed different (KD)

- Keys**
- Two nickel silver per lock cylinder

- Door Thickness**
- 1 3/8" – 2"

- Door Preparation**
- 2 1/8" diameter
 - 1" diameter for latchbolt

- Warranty**
- Lifetime limited

Light-Duty Tubular Grade 3

KT3500 SERIES

OPTIONS

KEYING 6-pin cylinders, can be pinned to 5-pin.

Cylinders Arrow A (ARA), Corbin 59A1 (C059A1), Corbin 60 (C06), Corbin Russwin L4 (CL4), Options Kwikset (KW1), Russwin D1 (RD1), Sargent LA (SAL), Schlage E (SCE), Schlage F (SCF), Weiser E (WRE), Yale 8 (YA8), Yale GA (YGA)

Tell Cylinder Restricted Tell keyway cylinder available, optional. Tell keyway cylinder is available only keyed to 6-pin.

Keying Options Grand Master Key (GMK), Construction Master Key (CMK), Master Key (MK), Keyed Different (KD), Keyed Alike (KA), Interchangeable Core uncombined (IC), 0-bitted (OBIT)

AVAILABLE FUNCTIONS Entry 81
Privacy Bed/Bath 76
Passage Hall/Closet 75

TELL FINISHES



US32D
Satin Stainless Steel